



# AFEX Bearing Equipment Co., Ltd.

7SRS15WGM[DD,DDHH,SS,SSHH,U  
U]C1+[57-1000/1]LM THK Miniature Linear  
Guide Full Ball SRS-G Accuracy and Preload  
Selectable

Bearing No.  
7SRS15WGM[DD,DDHH,SS,SSHH,UU]C1+[57-1000/1]L  
M

7SRS15WGM[DD,DDHH,SS,SSHH,UU]C1  
+[57-1000/1]LM Bearing 2D drawings and 3D CAD  
models

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	7
Nominal Part Number	15W
Rail Type	Wide Rail
Rail Width W1	42 mm
Mounting Height M	16 mm
Rail Length L	57 ~ 1000 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	7430
Basic Load Rating Static Rating Co(N)	8590
Allowable Static Moment MA(N m)	52.7
Allowable Static Moment MB(N m)	52.7
Allowable Static Moment MC(N m)	178
Symbols for Dust Resistance	UU: End Seals



## AFEX Bearing Equipment Co., Ltd.

Advanced Seal Options (Longer Leadtime)	SSHH: SS + Laminated Contact Scraper LaCS
Block external dimension W	60 mm
Block external dimension L	55.5 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	4.5 mm
Block dimension L1	38.9 mm