



AFEX Bearing Equipment Co., Ltd.

8SRS7WGN[SS,UU]+[33-300/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 8SRS7WGN[SS,UU]+[33-300/1]LM

8SRS7WGN[SS,UU]+[33-300/1]LM Bearing 2D
drawings and 3D CAD models

Days to Ship	27 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	8
Nominal Part Number	7W
Rail Type	Wide Rail
Rail Width W1	14 mm
Mounting Height M	9 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2120
Basic Load Rating Static Rating Co(N)	3660
Allowable Static Moment MA(N · m)	16.6
Allowable Static Moment MB(N · m)	19.2
Allowable Static Moment MC(N · m)	27
Symbols for Dust Resistance	UU: End Seals
Block external dimension W	25 mm
Block external dimension L	40.9 mm



AFEX Bearing Equipment Co., Ltd.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	30.3 mm